

Content (v.1.5)

1. Introduction
 - 1.1 The MPD experiment
 - 1.1.1 Perspectives for the research program of the MPD experiment
 - 1.2 The ALICE ITS2 first tracker totally based on MAPS Technology
 - 1.3 Tracking in the MPD
 - 1.3.1 The TPC
 - 1.3.2 The ITS
 - ITS Functions
 - Physics with the ITS
 - Production of low-momentum heavy hyperons and particles with open charm.
 - Production of hyper- and super-nuclei.
2. Pixel Chips
 - 2.1 The ALPIDE sensor from the ALICE ITS2
 - 2.2 Detector technology
 - 2.3 Principle of operation
 - 2.3.1 Particle detection
 - 2.3.2 Read-out
 - 2.4 Radiation hardness
3. Detector layout
 - 3.1 The two stages construction scenario
 - 3.2 Possibilities for the reduction of the beam pipe diameter
 - 3.3 Outer Barrel Stave
 - 3.4 Supporting mechanics
 - Material budget
 - Simulations results
 - 3.5 Integrated leak-less water cooling system
 - Material budget
 - Simulation results
 - 3.6 Integrated gas cooling system
 - Material budget
 - Simulation results
 - 3.7 Outer barrel FPC
 - 3.8 Pixel Chip to FPC connection
 - 3.9 Assembly procedures
 - 3.9.1 Outer Barrel HIC assembly
 - 3.9.1.1 HIC Test and characterization
 - 3.9.2 Outer Barrel Stave assembly
 - 3.9.2.1 Stave test and characterization
 - 3.9.3 The necessity for CMIS
 - 3.10 The MPD IT finalization after NICA LS1 (stage2: the Inner Barrel)
4. Support structure and system integration

- 4.1 Services
- 4.2 The beam pipe
- 4.3 Installation and Removal
- 5. The DAQ system
 - 5.1 Radiation environment
 - 5.1.1 Beam from the NICA collider
 - 5.1.2 Radiation levels in the detector regions
 - 5.2 The GBTx-emulating boards
 - 5.3 The receiver at the nodes of online farm (GbtX Emulator Readout Interface)
 - 5.4 Integration of the ITS DAQ into the MPD DAQ
- 6. The DCS
- 7. Detector performance
 - 7.1 The MPD TPC in a nutshell
 - 7.2 Simulations of the TPC – ITS tracking system
 - MPD beam pipe diameter variants: 40 cm & 64 cm
 - 7.3 Track reconstruction efficiency
 - (Full configuration (IB + OB) for a beam pipe diameter of 40 cm)
 - 7.4 Momentum resolution
 - 7.5 Phase space coverage for protons and pions
 - 7.6 Conclusions
- 8. Physics performance
 - 8.1 Simulation methods and conditions
 - Three configurations:
 - IB + OB for a beam pipe diameter of 40 cm (Complete project realization)
 - Only OB for a beam pipe diameter of 64 cm (First stage of the project)
 - IB + OB for a beam pipe diameter of 64 cm (in case of impossibility for beam pipe diameter reduction)
 - 8.2 Strange particles reconstruction
 - 8.2.1 Expected yields
 - 8.2.2 Transverse momentum coverage
 - 8.2.3 (...)
 - 8.3 Charmed particles reconstruction
 - 8.3.1 Expected yields
 - 8.3.2 Transverse momentum coverage
 - 8.3.3 Search for exotic particles and nuclei
- 9. Project organization and time lines